



GATO DE OLHAL P/CORRENTE C/PATILHA INTEGRADA EM AÇO ALLOY




REFERÊNCIA	CARGA DE TRABALHO kg	PARA CORRENTE mm	DIMENSÕES mm								PESO
			A	A1	A2	D	O	R	G	H	
FER-GCOA06	1.120	6	25,0	25,0	20,5	8,5	20,5	80,5	14,5	20,0	0,240
FER-GCOA07-8	2.000	7-8	29,5	25,5	24,5	11,0	25,0	95,5	19,0	27,0	0,530
FER-GCOA10	3.200	10	35,7	30,5	29,0	14,0	34,0	120,5	23,5	33,0	0,950
FER-GCOA13	5.400	13	43,5	41,0	35,4	17,5	42,5	150,0	29,0	40,0	1,670
FER-GCOA16	8.000	16	52,5	50,0	44,0	22,0	52,0	183,0	35,5	49,0	3,000
FER-GCOA19	12.000	19	62,5	60,0	54,0	25,0	62,0	217,5	42,0	55,0	5,400
FER-GCOA22	15.000	22	76,0	75,0	65,0	30,0	72,0	260,0	51,5	67,0	9,900

GATO DE FORQUETA P/CORRENTE C/PATILHA INTEGRADA EM AÇO ALLOY



REFERÊNCIA	CARGA DE TRABALHO kg	PARA CORRENTE mm	DIMENSÕES mm										PESO
			A	A1	A2	B	C	G	H	P	R		
FER-GCFA06	1.120	6	25,0	24,5	20,5	6,7	8,5	14,5	20,0	7,0	73,0	0,240	
FER-GCFA07-8	2.000	7-8	29,5	25,5	24,5	8,7	9,8	19,0	27,0	9,0	86,3	0,530	
FER-GCFA10	3.200	10	35,7	30,5	29,0	12,2	13,5	23,5	33,0	13,0	105,0	0,950	
FER-GCFA13	5.400	13	43,5	41,0	35,4	15,3	17,0	28,5	40,0	16,0	128,5	1,670	
FER-GCFA16	8.000	16	52,5	50,0	44,0	19,0	19,5	35,5	46,0	21,0	155,3	3,000	
FER-GCFA19	12.000	19	62,5	60,0	54,0	21,0	26,0	42,0	55,0	24,0	184,0	5,400	

GATO DE FUNDIÇÃO EM AÇO ALLOY



REFERÊNCIA	CARGA DE TRABALHO kg	PARA CORRENTE mm	DIMENSÕES mm						PESO
			A	D	O	R	G	H	
FER-GOFA07-8	2.000	7-8	63,0	12,0	13,0	120,0	26,0	31,0	1,100
FER-GOFA10	3.200	10	76,0	16,0	19,0	146,0	32,5	37,0	2,000
FER-GOFA13	5.400	13	89,0	19,0	25,0	174,0	40,0	45,0	3,100
FER-GOFA16	8.000	16	101,0	22,0	32,0	205,0	45,0	51,0	5,300
FER-GOFA20	12.000	20	114,0	25,0	38,0	235,0	60,0	68,0	9,100
FER-GOFA22	15.000	22	127,0	31,0	48,0	250,0	67,0	72,5	14,000